



Receptacle Holder

Plug Holder

Shell Size	Com'l	Mil. Ref.	Recommended Torque (+/- 5 Inch-Pounds)		A Dia. Max.	B Dia. Max.	C Dim. Max.
			Metal	Composite			
09		A	60	35	.577 (14.7)	.438 (11.1)	1.031 (26.2)
11		B	80	35	.709 (18.0)	.566 (14.4)	1.031 (26.2)
13		C	110	40	.829 (21.1)	.678 (17.2)	1.031 (26.2)
15		D	120	40	.954 (24.2)	.803 (20.4)	1.031 (26.2)
17		E	120	40	1.107 (28.1)	.928 (23.6)	1.031 (26.2)
19		F	120	40	1.190 (30.2)	1.033 (26.2)	1.031 (26.2)
21		G	140	80	1.315 (33.4)	1.158 (29.4)	1.031 (26.2)
23		H	140	80	1.440 (36.6)	1.283 (32.6)	1.031 (26.2)
25		J	140	80	1.565 (39.8)	1.408 (35.8)	1.031 (26.2)

**NOTES**

1. Metric dimensions (mm) are indicated in parentheses.
2. Material: Case hardened carbon steel with electroless nickel finish.
3. Receptacle and plug holder drives: 1/4" - Shell sizes 09, 11 and 13; 3/8" - Shell sizes 15 and up.
4. Composite values apply when using Glenair 600-091 and 600-007 tools.